# FEATURES AND SPECIFICATIONS

# molex PowerCat 45 x 45 mm Module FTP Category **5E**

# **Features and Benefits**

The 45 x 45mm module has been designed specifically to be compatible with the Legrand range of 45 x 45mm bezels. Molex's PowerCat 45 x 45mm module features an enhanced performance Category 5, RJ45 RJLP connector, designed to support high speed data transmission. The module is part of the PowerCat System range of products, that have been designed based on the PowerSum principle of crosstalk measurement and testing.

Molex Premise Networks unique patented RJLP RJ45 connector is designed to meet the highest performance standards in the industry and offers a low profile, space saving design that enables installation in shallow backboxes and trunking. The FTP connector provides continuity of the cable shield by providing a termination point for the drain wire.

- Legrand bezel compatible
- Enhanced Performance RJ45 connector
- EIA 568B wired
- Provides through shield continuity

### **Technical Information Mechanical Characteristics**

Termination Tools: Molex and other industry standard installation tools

#### **IDC** Terminations

Suitable for 0.4mm - 0.6mm solid or stranded cable, maximum o.d 1.5mm Two wires may be terminated for daisy-chain applications. Patents pending on connector and module designs.

Jack Connector	
Operating Life :	Minimum 500
	insertion cycles
Contact Material	Phosphor Bronze
Contact Plating :	1.25 micrometres
	Au/Ni
Material :	UL 94V0 Thermoplastic

#### **IDC** Connector 1:4

Operating Life :	Minimum 100
	Reterminations
<b>Contact Material</b>	:Phosphor Bronze
Contact Plating :	Sn/Pb over Ni
Wire Accommoda	tion :2 x 22-26 AWG
	solid or stranded

. . . .

- - -

# **Electrical/Optical Characteristics**

D.C. Resistance :  $<20m \Omega$ D.C. Resistance Imbalance :  $<2.0m \Omega$ Insulation Resistance: >100M  $\Omega$ Attenuation (dB) @ 1MHz 0.0121 @ 16MHz 0.0193 @ 100MHz 0.1052 Crosstalk (dB) @ 1MHz -84.24 -60.03 @ 16MHz @ 100MHz -45.70 PowerSum Worst Pair @ 100MHz -41.83 Return Loss (dB) @ 1MHz -65 @ 16MHz -48 @ 100MHz -30

Backbox/Trunking depth requirement Minimum clearance 16mm

# **ORDERING INFORMATION**

Order No.	SAP No.	Description
MLG-00005-02	Consult Molex	45 x 45mm FTP Module 568B Cat 5E White Powercat

Molex Premise Networks standard fascia colour is white. Other colours may be subject to minimum order quantities.

# **MOLEX PREMISE NETWORKS**

Americas Tel: 630 969 4550 www.molexpn.com

ΕΜΕΔ Tel: 44 (0)2392 205800 www.molexpn.co.uk

APAC Tel: 61 3 9971 7111 www.molexpn.com.au

©2014, Molex Premise Networks Printed in the UK Form#MLG-00005-02 Page 1 Issue 1 This information is correct at the time of publication, specifications are subject to change