



## Power over Ethernet (PoE) Injector TPE-1011 (v2.0R)

TPE-1011 Power over Ethernet Injector provides an innovative and cost effective solution to a variety of Ethernet devices such as VoIP phones or Wireless Access Points. Reduce costs by using existing CAT5 cable to deliver both power and data where power source is difficult to obtain.

### FEATURES

- Compliant with IEEE 802.3af Power over Ethernet (PoE) Standard
- Reduce Cabling for Wireless APs, IP Phone and any IEEE 802.3af Powered Device (PD)
- Supplies Power to PD up to 15.5 Watts
- Automatically Detecting PoE Terminals and Supplying Inline Power
- Advanced Auto-Sensing Algorithm Giving Power only to 802.3af end device
- High Safety Standards with Short Circuit Protection
- Supports Power Detection and Classification
- 5-Year Warranty



# Power over Ethernet (PoE) Injector

## TPE-101I (V2.0R)

### SPECIFICATIONS

Hardware	
Standards	• IEEE 802.3 10Base-T • IEEE802.3u 100Base-TX • IEEE 802.3af Power over Ethernet
Network Media	• 10Mbps: UTP/STP Cat. 3, 4, 5; Up to 100 Meters • 100Mbps: UTP/STP Cat. 5; Up to 100 Meters
Protocol	• CSMA/CD
Topology	• Star
Ports	• 1 x DATA-IN Port (Data only) • 1 x PoE-OUT Port (Data + Power)
Data Lines	• Pair 1: Pin 1, 2 • Pair 2: Pin 3, 6
Power	• Input: Power supply: AC 100~240V, 50~60Hz, 0.3A • Output: Class 0, 48V DC @ 15.4 watts ; Class 1, 48V DC @ 4 watts ; Class 2, 48V DC @ 7 watts ; Class 3, 48V DC @ 15.4 watts
Diagnostic LEDs	• Power: Green
Power Consumption	• 15.5 Watts
Temperature	• Operating: 0°~ 45°C (32°F~ 113°F) • Storage: -40°~ 70°C (40°F~ 158°F)
Humidity	• 10%- 90% (non-condensing)
Dimensions (LxWxH)	• 115 x 57 x 35mm (4.5 x 2.2 x 1.4 in.)
Weights	• 325g (11.6oz.)
Certification	• FCC, CE

### NETWORKING SOLUTIONS



### PACKAGE CONTENTS

- TPE-101I
- Multi-Language User's Guide
- Power Adapter (48VDC, 0.5A)

### RELATED PRODUCTS

<b>TPE-102S</b>	Power over Ethernet (PoE) Splitter
<b>TPE-S88</b>	16-Port 10/100Mbps Web Smart PoE Switch

### ORDERING INFORMATION

**TRENDNET®**

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: [www.trendnet.com](http://www.trendnet.com)

Email: [sales@trendnet.com](mailto:sales@trendnet.com)

To Order Please Call:

**1-888-326-6061**

