

# VTH1560B/BW

IP Indoor Monitor



## Technical Specification

Model	VTH1560B/BW
-------	-------------

### System

Main Processor	Embedded Micro Processor
----------------	--------------------------

Operation System	Embedded LINUX OS
------------------	-------------------

### Video

Video Compression	H.264
-------------------	-------

### Audio

Audio Compression	G.711
-------------------	-------

Audio Input	All-direction Microphone
-------------	--------------------------

Audio Output	Built-in Loudspeaker
--------------	----------------------

Bidirectional Talk	Support Dual-way Bidirectional talk
--------------------	-------------------------------------

### Display

LCD Screen	7" 800x480, Capacitive
------------	------------------------

### Operation Mode

Input	Touch buttons
-------	---------------

### Interface

Alarm In	8
----------	---

Alarm Out	-
-----------	---

RS485	-
-------	---

### Network

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------

### General

Memory Slot	Embedded 4GB
-------------	--------------

## Features

- 7" TFT Capacitive touch screen
- IPC surveillance
- Alarm integration
- Embedded 4GB SD card
- Record & Snapshot



### Installation

### Flush

Power	DC 12V/ supply directly by VTNS1060A
-------	--------------------------------------

Power Consumption	Standby ≤1.5W, Work ≤7W
-------------------	-------------------------


Working Temperature	-10°C~+55°C
---------------------	-------------

Relative Humidity	10%~90%RH
-------------------	-----------


Dimensions	221.2mm×154.3mm×24.2mm
------------	------------------------

Weight	0.8Kg
--------	-------

Dimensions



View Area



Application

