

AXIS Camera Station S1016 Mk II Recorder

Out-of-the box ready workstation for high-definition surveillance

AXIS Camera Station S1016 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. It is preloaded with AXIS Camera Station video management software with universal licenses for 16 channels and other necessary system software. It is preconfigured to minimize installation time. AXIS S1016 has validated hardware components and extendable storage capacity, and includes three-year hardware warranty with on-site replacement service. AXIS Camera Station offers an intuitive user interface and allows users to take full advantage of Axis' wide range of video surveillance cameras and other IP products. It also supports integration of third party IP cameras.

- > Ease of installation
- > Validated with extensive support
- > High-definition surveillance up to 4K
- > AXIS Camera Station included
- > Full compatibility with Axis' products







AXIS Camera Station S1016 Mk II Recorder

Licenses	16 AXIS Camera Station universal licenses included, can be upgraded up to 32 licenses (sold separately)
Processor	Intel® i5 4570S, Quad Core, 2.90 GHz Turbo, 6MB
Memory	8GB (2x4GB) 1600 MHz DDR3
Storage	8 TB (2x4TB) Enterprise Class HDD, 7200 rpm, SATA 6Gb/s , no RAID. Possible to add 2 additional HDDa $$
Graphic card	AMD Radeon R5 340X 2 GB 2 monitors supported
Operating system	Microsoft Windows 10 IoT Enterprise
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view Playback: 4 x 1080p camera split views or 1 x 4K camera view
Recording	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
General	
Power	Max 365 W, 100 V AC to 240 V AC
Connectors	6xUSB 2.0, 4xUSB 3.0, 1xDisplay Port, 1xDual link DVI-I Ethernet LAN 10/100/1000 Mbit, Line-in/out connectors, Computer mouse and keyboard connectors
Operating conditions	5 °C to 45 °C (41 °F to 113°F)

Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EN/IEC/UL 60950-1, FCC part 15, class B, VCCI V-3, VCCI V-4, AS/NZS CISPR 22, class B, ICES-003/NMB-003, KCC KN22 Class B, KN-24,EN 62311, EN 55022, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 300 328, EN 301 893, EN 301 489-1, EN 301 489-17
Dimensions	360 x 175 x 417 mm (14.17 x 6.89 x 16.42 in)
Weight	9.5 kg (20.9 lb)
Included accessories	Installation guide, Keyboard (International/US), Computer mouse, Power cable
Optional accessories	AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller AXIS Camera Station S9001 MklI Desktop Terminal AXIS Camera Station S9002 Desktop Terminal
Warranty	Axis 3-year warranty, see www.axis.com/warranty

a. For more info www.axis.com/support

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on *www.axis.com*

Environmental responsibility: www.axis.com/environmental-responsibility

