

# VTO2111D-WP

# 1MP Wi-Fi Villa Outdoor Station



Technical Specification	
Model	VTO2111D-WP
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/4" 1MP CMOS
Lens	2.2mm
Angle of View	D:125° H:105°
Day/Night	ICR
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Operation Mode	
Keypad	Single Mechanical Button
Reader	Mifare Card
Interface	
Door Control	$2(1\mbox{relay}$ out for main lock, $1\mbox{extended}$ by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1
Network	

IEEE802.11b/g/n

Wi-Fi

### Features

- HD CMOS camera
- · Large field of view angle
- · Night vision
- · Voice indication
- · Remote intercom with mobile APP
- · Surface mounted












thernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP


#### General

General	
Ingress Protection	IP65
Tamper Switch	1
Memory Slot	Micro SD, Max 32G
Installation	Surface & Flush
Material	Plastic
Power	DC 12V,PoE(802.3af)
Power Consumption	Standby ≤1W, Work ≤10W
Working Environments	-30°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	135mm×70.4mm×34.4mm
Weight	0.4Kg

#### **Dimensions**

# **View Area**





# Application

#### 1 – Smart Doorbell

Call Mobile phone APP directly without indoor monitor



# 2 – Video Intercom

Color video & audio call IPC surveillance Alarm integration Remote intercom with mobile APP

