


AXIS A4010-E Reader

Generic touch-free reader

AXIS A4010-E Reader without Keypad is a joint cooperation between Axis and ASSA Abloy designed to perfectly match AXIS A1001 Network Door Controller. The cost-efficient reader has no keypad and its small form factor enables easy placement. Two LED symbols give clearly visible feedback. The reader supports touch-free entry with most entry card formats, and is suitable for both indoor and outdoor installation. IP65 classification makes it ready for harsh environments.

- > Designed to perfectly match AXIS A1001
- > Support for most smart card formats
- > 2 LED symbols give clearly visible feedback
- > Indoor and outdoor ready
- > IP65 classified





www.cxis.com T10076308/EN/M5.2/1802

AXIS A4010-E Reader

Compatible AXIS A1001 Network Door Controller products Indications and user interface Entry Card, Tag authentication Read range 30-40 mm with recommended cards and tags Alarm status Symbols for: Access granted, Access denied indication General Casing ABS and halogen free halon plastic Generic 13,56 MHz (MIFARE Classic, MIFARE Plus (Level 1 and 3), MIFARE DESFire EV1, iCLASS® CSN and iCLASS® SEOS™a Reader technology Communication RS-485 - OSDP Power 12-24V DC max 2.8 W Translates to 240 mA@12V Operating -30 °C to 70 °C (-34 °F to 158 °F) conditions Storage -50 °C to 70 °C (-58 °F to 158 °F) conditions Approvals EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN 55024, EN 50130-4, CFR part 15 Subpart C, AS/NZS 4268, RSS-GEN, RSS-210, EN 50581, EN/IEC 60950-22, ETSI EN 300 330-1, ETSI EN 300 330-2, UL294 Dimensions 85 x 46 x 19 mm (3.35 x 1.8 x 0.75 in) Cable length: 3 m Weight 128 g (0.28 lb)

Axis 3-year warranty, see www.axis.com/warranty

a. Extra configuration card needed, sold separately.

Environmental responsibility: www.axis.com/environmental-responsibility

Warranty

