

Passive HDCVI Balun



- One (1) Channel Balun
- Real-time Transmission over UTP CAT 5E/6 Cable
- Passive Balun

Technical Specifications

Video

Transmission Signal	One (1) Channel
Transmission Distance, maximum	HDCVI 720p: 400 m (1312.34 ft) 1080p: 250 m (820.21 ft) 4 MP: 200 m (656.17 ft)
Category Type	UTP CAT 5E/6

Video Transmission Properties and Ports

Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Push-terminal
Compatible Format	HDCVI, AHD, TVI, CVBS
Resolution	720p, 1080p, 4 MP
Anti-interference	> 60 dB

Protection

ESD	1a contact discharge electricity level 3 1b air discharge electricity level 3 Per: IEC61000-4-2
Coaxial Cable Connector	2 KV (common-code) per IEC1000-4-5
UTP Cable Connector	2 KV (different-code), 4 KV (common-code), per IEC1000-4-5

Impedance

BNC Male	75 Ω
UTP Cable	100 Ω

Physical Properties

Dimensions	173.0 mm x 21.0 mm x 20.0 mm (6.81 in. x 0.83 in. x 0.79 in.)
Shell	ABS
Color	Black
Net Weight	0.25 kg (0.06 lb)

Stability

MTBF	> 10000 h
------	-----------

Environmental

Operating Temperature	-10 °C to +55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to +70 °C (-4 °F to 158 °F)
Humidity	0 to 95%, non-condensing