

AXIS Q6054-E PTZ Dome Network Camera

Outdoor-ready PTZ with 30x zoom and focus recall

AXIS Q6054-E is a top-of-the-line PTZ dome, offering fast and precise pan/tilt performance for wide area coverage and detailed surveillance at great distances. The focus recall feature offers instant focus in predefined areas. The high light sensitivity and day/night functionality ensure high image quality even in low-light conditions. Axis Zipstream technology reduces bandwidth and storage requirements, while Arctic Temperature Control ensures safe startup in extreme cold. AXIS Q6054-E also offers shock detection, video motion detection, electronic image stabilization, automatic defog, and Active Gatekeeper.

- > [High light sensitivity](#)
- > [HDTV 720p and 30x optical zoom](#)
- > [Focus recall](#)
- > [Axis Zipstream technology](#)
- > [Vandal-resistant](#)



AXIS Q6054-E PTZ Dome Network Camera

Models	AXIS Q6054-E 60 Hz AXIS Q6054-E 50 Hz	Notification via email, HTTP, HTTPS and TCP
Camera		
Image sensor	1/3" progressive scan CCD	Data streaming Event data
Lens	4.4–132 mm, F1.4–4.6 Horizontal field of view: 62.9°–2.2° Vertical field of view: 37°–1.2° Autofocus, auto-iris	Built-in installation aids Pixel counter
Day and night	Automatically removable infrared-cut filter	General
Minimum illumination	Color: 0.2 lux at 30 IRE F1.4 B/W: 0.04 lux at 30 IRE F1.4 Color: 0.3 lux at 50 IRE F1.4 B/W: 0.05 lux at 50 IRE F1.4	Casing IP66-, NEMA 4X- and IK10-rated Metal casing (aluminum), polycarbonate (PC) clear dome, sunshield (PC/ASA)
Shutter time	1/10000 s to 1/4 s	Sustainability PVC free
Pan/Tilt/Zoom	Pan: 360° endless, 0.05° – 450°/s Tilt: 220°, 0.05°–450°/s 30x optical zoom and 12x digital zoom, total 360x zoom E-flip, 256 preset positions, Tour recording, Guard tour, Control queue, On-screen directional indicator, Set new pan 0°, Adjustable zoom speed	Memory 512 MB RAM, 256 MB Flash
Video		Power Axis High PoE midspan 1–port: 100–240 V AC, max 74 W Camera consumption: typical 16 W, max 60 W
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Connectors RJ45 10BASE-T/100BASE-TX PoE, RJ45 Push-pull Connector (IP66) included
Resolution	HDTV 720p 1280x720 to 320x180	Storage Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	Operating conditions With 30 W midspan: -20 °C to 50 °C (-4 °F to 122 °F) With 60 W midspan: -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology Controllable frame rate and bandwidth VBR/MBR H.264	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Image settings	Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation Electronic Image Stabilization (EIS) Wide Dynamic Range (WDR)	Approvals EMC EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1 IEC/EN/UL 60950-22 Environment EN 50121-4, IEC 62236-4, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, NEMA 250 Type 4X IEC/EN 60529 IP66 IEC 60721-4-3, IEC 60068-2-30, IEC 60068-2-60, IEC 60068-2-78, NEMA TS-2-2003 v02.06, Subsection 2.2.7, 2.2.8, 2.2.9; IEC 62262 IK10, ISO 4892-2 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR
Network		Weight 3.7 kg (8.2 lb)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Dimensions Ø232 x 280 mm (Ø9 1/8 x 11 in)
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, LLDP	Included accessories Axis High PoE 60 W midspan 1–port, RJ45 Push-pull Connector (IP66), Sunshield Installation Guide, Windows decoder 1-user license
System integration		Optional accessories Smoked dome cover AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
Analytics	AXIS Video Motion Detection, Autotracking, Active Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Event triggers	Detectors: live stream accessed, video motion detection, shock detection Hardware: fan, network, temperature, casing open PTZ: autotracking, error, moving, ready, preset reached Storage: disruption, recording System: system ready Time: recurrence, use schedule Input signal: manual trigger, virtual input	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Event actions	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

www.axis.com/environmental-responsibility