

DH-MCVR6204 4 Channel Mobile HDCVI Video Recorder



- Support HDCVI/Analog Video input
- H.264 dual-stream video compression
- Support 4 ch 1080P realtime recording
- VGA/TV simultaneous video output
- Support 2 SATA HDD, 2 USB3.0
- Aviation connectors adopted
- Multiple monitoring: Web viewer, CMS(DSS) & DMSS



System Overview

MCVR6204 is the first mobile video recorder which adopts the HDCVI technology, it can support 1080P high-definition real-time recording, it can support real-time vehicle location tracking and monitoring, and all the information such as GPS and video can be uploaded by wireless network: 3G/4G/WIFI.this device can also support to connect various accessorie, such as card reader, fuel sensor, emergency button. It has already pass EN50155/ISO16750 in order to meet the requirements of mobile use.This device can be used in kinds of solutions for different applications, such as city bus/school bus/taxi/police car/train/ truck.

Functions

Anti-vibration

Using shock-absorbing material and structure, the new designed hard disk box can cope with varying degrees of vibration, keeping the system work normally all the time.

Wide range of power supply

As the voltage output of vehicle battery changes during driving, the wide range of power supply can protect the device.

3G/4G/WIFI

Embedded with 3G/4G/WIFI module, the device can register into a public network to connect with VMS, and can send all the information(video/audio/alarm/gps) through wireless network.

GPS

Embedded GPS module can receive location information and upload to VMS, and the vehicle can be tracked on the electric map of VMS.

Multiple ports

With kinds of ports, like CAN, RS232, RS485, I/O, the video recorder can connect with various of accessories, such as card reader, fuel sensor, panic button and so on.system), so that the video, audio, alarm and location information can be uploaded to VMS.

Mobile HDCVI Series | DH-MCVR6204

Technical Specification

Storage Internal HDD

SD card


reennear opeennearion	
System	
Main Processor	Embedded microprocessor
Operating System	Embedded LINUX
Audio and Video	
Input	4 Channel (Don't support audio in when connecting analog cameras)
Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Display	
Interface	1VGA, 2TV (1 aviation connector)
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600
Display Split	1/4/8/9
Privacy Masking	4 rectangular zones (each camera)
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Video/Audio Compression	H.264/G.711
Resolution	4 ch@1080P realtime recording
Bit Rate	48~8192Kb/s
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	9 channels, Alarm 1-Alarm 7 is the local alarm input. Alarm 8/9 is pulse input.
Relay Output	2 channel
Playback and Backup	
Playback	1/4
Search Mode	Time/Date, Alarm, Motion Detection & Exact search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network

2 SATA Ports

1 SD card, Up to 128 GB

Network	
Ethernet	RJ-45 Port (10/100/1000Mbps)
Wireless Network	Built-in 3G/4G/Wi-Fi module(optional)
GPS	Built-in high accurate GPS module(optional)
Network Function	TCP/IP, UDP, DHCP, DDNS, FTP, Email, Alarm Server
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Auxiliary Interface	
USB	3 Ports (1 rear), 2 USB 3.0
RS232	2 Ports, for PC Communication and Keyboard
RS485	2 Ports, for PTZ Control
CAN	Support
Heater	Optional
Electrical	
Power Supply	DC 6V~36V
Power Consumption	<12W (Without HDD)
Environmental	
Operating Conditions	-30°C (with heater)~ +60°C (+14°F ~ +131°F)
Storage Conditions	-30°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Construction	
Dimensions	180mm×190mm×50mm (7.0" x 8.7" x 2.0")
Net Weight	2.2kg (4.6 lb) (without HDD)
Certifications	
CE	FCC
EN50155	ISO16750

Dimensions (mm)



Rev 001.001 2016 Dahua. All rights reserved. Design and specifications are subject to change without notice.