

# DHI-ASL7112R DHI-ASL7112S

## Smart lock



### Features

- 4 Ways opening : cards & fingerprints & passwords & Emergency Keys
- Privacy password: xxx+password+xxx, preventing password to be seen by others
- Passage Mode and Non-disturbance Mode optional and Silence Mode
- Auto lock when come across a consecutive invalid passwords or cards or fingerprints
- Low Power Alert (<4.5V)
- Huge storage: 100 cards, 100 passwords, 100 Fingerprints,
- Battery life more than 14 months (10 Units/D)
- Emergency power supply outside
- Two colors optional
- Zinc alloy material

### Technical Specification

#### Card

Card Type	Mifare 1
Card Features	Contactless, high security, all-in-one possible
Sensor Distance	< 20mm
Sensor Time	< 0.5s
Storage Capacity	100

#### Password

Keypad Type	Multi-touch keypad
Password Length	6-12 bits
Storage Capacity	100

#### Fingerprint

Sensor	Optical
Prevent fake	Live detection
False Rejection Rate	≤0.92%
False Accept Rate	≤0.0002%
Fingerprint Capacity	100

#### Battery

Working Voltage	DC4.5V~6.5V 4*1.5V"AA"battery
Battery Life	At least 14 Months (10 units/D)
Low Battery Warning	< DC4.5V
Emergency Power Supply	Micro USB

#### Structure

Door Thickness	40-90mm (customizable)
Position Dimension	Door margin 60mm, central distance 68mm
Lock Body	European standard
Product Standard	GA701-2007
Material	Zinc alloy

#### General

Working Temperature	-10°C~+55°C
Relative Humidity	10%~93%
Salt spray test	≥200h
Lock case test	≥100000 times
Package size	422*259*157(mm)
Gross weight	4.12Kg
Restore Default	Support
Reset	Support
Ring	Support
Built-in Loudspeaker	Support
Built-in Buzzer	Support

# DHI-ASL7112R DHI-ASL7112S

## Selection

	DHI-ASL7112R	Antique copper
	DHI-ASL7112S	Satin silver

## Dimensions

