

DHI-LM32-S200

32" FHD Monitor



Features :

- Professional thermal design to extend equipment lifespan
- Using tamper-proof metal housing
- 8ms fast response time for no motion blur, judder or ghosting
- Built-in 3D COMB filter and 3D noise reduction
- High fidelity digital processing for a brilliant and vivid video
- Infrared, RS232 double mode, supporting remote PC control
- Support multiple signals, such as HDMI, DVI, VGA, BNC, USB multimedia, Audio, RS232



Technical Specification

Model

Model	DHI-LM32-S200
-------	---------------

Display

Screen Size	31.5"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	350 cd/ m ²
Contrast	1200:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RS232×1, USB×1	
Output	CVBS(BNC)×2, RS232×1	
	Speaker	2W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	35W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	10kg (22.0lb)	
Gross Weight	14kg (30.9lb)	
Bezel Width	25.5mm (U/L/R/B)	
Wall Mount	300×300mm (11.8"×11.8")	
Dimension without standard (W×H×D)	750.7×455.1×44.0mm (29.6"×17.9"×1.7")	
Package(W×H×D)	872×585×162mm (34.3"×23.0"×6.4")	
Work Environment	Temperature	0 C~50 C (32°F~122°F)
	Humidity	20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

